

CIRQUE

120V PENDANTS

location: DAMP

SPECIFICATIONS:

DESCRIPTION

6-light suspension pendant with wooden ring.

LAMPING

Standard: 60W Medium-based 120V, lamp not included. Dimmable with standard incandescent dimmer (not included).

LED Filament: 8W Replaceable A19 LED Filament lamp, 120V, dimmable, 80+ CRI, 3000°K CCT, 800 lumens, 15,000 hours, lamp included.

SUSPENSION

Cloth cords with Black sockets on $28^{\prime\prime}$ Wood Ring. Available with Mesh Shade option.

CANOPY


6-light canopy. Plated stamped steel construction.

MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only). Consult factory concerning lower wattage labeling for energy requirements.





CIRQUE-120V-BK-MS (CIRQUE WITH MESH SHADES)


CIRQUE-120V-SL SILVER CORDS CIRQUE-120V-SL SILVER CORDS

ORDERING:

FIXTURE	- TYPE -	LAMP OPTIONS -	CORD	- OPTION
CIRQUE Cirque	120V 120V	(blank) 60W Incan	BK Black	MS Mesh
		EDIL 8W LED Filament	RD Red	Shade
			SL Silver	

Ex. CIRQUE-120V-RD

Cirque Suspension, 120V Type, Red Cord Black Finish



All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 9/22