

# \*\*\*READ & SAVE THESE INSTRUCTIONS \*\*\*

## MODEL 20370MG

### INSTALLATION & OPERATION INSTRUCTIONS

#### 1) TOOLS AND MATERIALS REQUIRED

- ❖ Blade Screwdriver
- ❖ Adjustable Wrench
- ❖ Wire Cutters
- ❖ 2 x 60W/E-26/Bulbs

#### **Attention:**

***Before assembling your lighting fixture, please read the following instructions.***

#### (2) GENERAL

1. To ensure the success of the installation, be sure to read these instructions thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
3. These fixtures are intended for mounting to a standard 4" x 2 1/4" deep metal octagon outlet box. The box must be directly supported by the building structure and must be U.L. Recognized
4. Before commencing with the installation, ***disconnect the power by turning off the circuit breaker*** or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

#### **NOTE:**

***The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. The person(s) caring for and operating the fixture must supply these factors.***

#### (3) UNPACKING THE FIXTURE

On checking the contents of the box you will find;

1. Universal Crossbar
2. Fixture Assembly
3. Mounting Hardware packet
4. 1 x Glass Diffusers

#### (4) PREPARE THE FIXTURE

1. If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
2. Place the supplied long screws through the holes in the crossbar and facing outward.
3. Secure crossbar to outlet box with the supplied short screws. (The long screws should be facing out from the wall).
4. Connect the Black wire from the fixture to the Black supply wire and the White fixture wire to the White supply wire, fasten securely with supplied wire nuts and secure wire nuts with UL listed electrical tape (not supplied). Tuck the wires carefully into the Junction box.
5. Connect the ground wire from the fixture to the electrical supply ground wire, or attach the ground wire directly to the ground screw on the crossbar. Fasten securely with supplied wire nuts and secure wire nuts with UL listed electrical tape (not supplied). Tuck the wires carefully into the Junction box.
6. Put the long screws through the 2 holes allocated in the fixture back plate. Secure the fixture against the wall by screwing on the supplied nut caps.
7. Insert the bulbs. **DO NOT EXCEED THE WATTAGE AS INDICATED ON THE WARNING LABEL.**
8. Place the metal frame over the glass diffuser (5) onto the fixture back plate and secure by screws at corners. Place fixture cover on top of metal frame and aligning the two holes on the left and right hand side of the fixture. Secure with the supplied screws.
9. It is strongly recommended that you caulk this fixture around the back plate, where it makes contact with the wall.

#### **CAUTION:**

- ***Ensure that the Fitting is Cool and Switched off, Before Changing Bulbs.***
- ***Do Not use Bulbs Exceeding Maximum Wattage as Per Caution Label.***
- ***Do Not Touch the Bulb while fixture is in operation.***
- ***Do Not place fixture in close proximity to any combustible material.***



# MODEL 20370MG

